

FAMILY	FORM FACTOR	MOTOR TYPE	VOLTAGE	CURRENT	NETWORK COMMUNICATION	FEEDBACK			
DIGITAL	FLEXPRO	BRUSHED	10-90 VDC	5-60 A Cont.	EtherCAT	Biss C-MODE			
		BRUSHLESS		10-100 A Peak	CANOpen	Halls			
		PCB MOUNT		10-100 A Peak	RS-485/232	Inc. Encoder			
		STEPPER		5-60 A Cont.	EtherCAT	Tachometer			
		AC INDUCTION		10-100 A Peak	CANOpen	Biss C-MODE			
		MACHINE EMBEDDED		5-60 A Cont.	EtherCAT	Halls			
	DEVELOPMENT BOARD	BRUSHLESS	10-90 VDC	5-60 A Cont.	CANOpen	Inc. Encoder			
		STEPPER		10-100 A Peak	RS-485/232	Tachometer			
		AC INDUCTION		5-60 A Cont.	EtherCAT	Biss C-MODE			
		BRUSHED		10-100 A Peak	CANOpen	Halls			
		PANEL MOUNT		25 A Cont.	EtherCAT	Inc. Encoder			
		STEPPER		50 A Peak	Ethernet/IP	Tachometer			
	DIGIFLEX	PCB MOUNT	BRUSHED	10-170 VDC	10-50 A Cont.	CANOpen	Halls		
			BRUSHLESS			Modbus RTU	Inc. Encoder		
			STEPPER			RS-485/232	+/-10 VDC Pos.		
			AC INDUCTION		20-100 A Peak	DxM Technology	Tachometer		
			PANEL MOUNT		BRUSHED	20-747 VDC	10-50 A Cont.	EtherCAT	1Vp-p Sine/Cosine Encoder
					BRUSHLESS			Ethernet	Biss C-MODE
STEPPER		Ethernet POWERLINK		EnDat 2.1					
AC INDUCTION		20-100 A Peak		Modbus TCP	EnDat 2.2				
VEHICLE MOUNT		BRUSHED		20-80 VDC	125-150 A Cont.		CANOpen	Halls	
		BRUSHLESS					Modbus RTU	Inc. Encoder	
		STEPPER	RS-485/232			+/-10 VDC Pos.			
		AC INDUCTION	200-250 A Peak		EtherCAT	Tachometer			
	PCB MOUNT	BRUSHED	10-175 VDC		3-30 A Cont.	Ethernet	1Vp-p Sine/Cosine Encoder		
		BRUSHLESS				Ethernet POWERLINK	Biss C-MODE		
STEPPER		Modbus TCP		Resolver					
AC INDUCTION		100-480 VDC		20-100 A Peak	EnDat 2.2				
VEHICLE MOUNT		BRUSHED		20-175 VDC	80-150 A Cont.	CANOpen	Halls		
		BRUSHLESS				100-250 A Peak	Inc. Encoder		
	STEPPER	200-250 A Peak	Tachometer						
	AC INDUCTION	125-150 A Cont.	200-250 A Peak		+/-10 VDC Pos.				
	ANALOG	PCB MOUNT	BRUSHED		10-175 VDC	3-30 A Cont.	Halls		
			BRUSHLESS			6-60 A Peak	Inc. Encoder		
STEPPER			Tachometer						
PANEL MOUNT		BRUSHED	20-400 VDC	7.5-50 A Cont.	Halls				
		BRUSHLESS		45-265 VAC	15-100 A Peak	Inc. Encoder			
		STEPPER		80-150 A Cont.	Tachometer				
VEHICLE MOUNT	BRUSHED	20-175 VDC	80-150 A Cont.	Halls					
	BRUSHLESS		100-250 A Peak	Inc. Encoder					
	STEPPER		100-250 A Peak	Tachometer					

• Any: Controller, Motor, Feedback, Application, Network, Environment, Industry.

